

LED MIRROR COLOR TEMPERATURE

Compare the room, light role and control state - not Kelvin alone

Use one controlled reference from early shortlist through sample review and written quotation.

PROGRAM / BUYER	PRODUCT / ROOM TYPE	DRAWING / SAMPLE REV.	DESTINATION / REVIEWER

WARMER DIRECTION

Starting range for room concepts that call for a warmer appearance. Coordinate with finishes and other luminaires.

2700-3000 K

NEUTRAL DIRECTION

Starting range for balanced project or retail comparisons. Approve beside the actual room-light reference.

3500-4000 K

COOLER DIRECTION

Use only where the buyer task, room concept and surrounding lighting support the cooler appearance.

5000 K +

ITEM / ROOM	LIGHT ROLE	CCT / MODE	ROOM REFERENCE	CONTROL STATE	SAMPLE STATUS	SUPPLIER RETURN / OPEN ITEM
Code, room type, drawing rev.	Front / back / dual; task or ambient priority.	Kelvin value; fixed or selectable settings.	Ceiling / wall / vanity light and finish reference.	Control method; default; memory; zone sync.	Shortlist / sample / approved / revise.	Output, rendering, electrical, documents or evidence to confirm.

APPROVAL CHECK	☐ Room reference reviewed	☐ Kelvin / mode recorded	☐ Control state recorded	☐ Sample tied to drawing revision	☐ Open supplier items listed
----------------	--	---	---	--	---